



## D4-800-2/D4-1100-2/D4-1300-2

LOGICAL INNOVATION FOR PICK AND PLACE ROBOTICS

The Codian Robotics D4-800-2/1100-2/1300-2 three- or four-axis delta robots are ideal for high speed toploading pick & place processes.

The parallel kinematics design is clean, fast and silent. These robots are designed to perform with payloads up to 3 kg and have a working envelope of 800/1100/1300 mm. The robots can be controlled by various industry standard motion control systems. Combined with a vision system, they can also be used for random and/or mixed product flow picking.

- Open platform for servo motors and control systems
- Designed for applications up to 15G
- ISO mount gripper interface
- Materials: carbon fibre, stainless steel, anodized aluminium, titanium, plastic
- Zero footprint
- Low maintenance, easy access to components



**CODIAN**  
ROBOTICS

## D4-800-2/D4-1100-2/D4-1300-2

THE NEW STANDARD FOR PICKING AND PLACING

### SPECIFICATIONS

Kinematic structure:	delta type
Degrees of freedom:	3+1*
Protection:	IP 65
Noise level:	< 68 dB(A)
Weight:	65 kg

\*with optional rotation axis

### PERFORMANCE

Rated working range:	ø 800/1100/1300 x 250 mm (see drawing)
Payload (max.):	3 kg
Pick and Place actions (D4-800-2/1100-2/1300-2):	max. 200/180/150 p/min
Position repeatability X,Y,Z:	± 0.1mm
Rotation axis Rz (optional):	angle unlimited angular repeatability Rz ± 0.3 ° limitation rotation axis torque 16Nm

### WORKING AREA

